

Video Standard	HD & SD
Video Format	1080p 50/59.94/60Hz 1080i 50/59.94/60Hz 720p 50/59.94/60Hz 576i/p 50Hz 480i/p 59.94Hz
Video Input	3 x HDBaseT 1 x HDMI
Computer Graphics Interface	1 via HDMI (Lumakey)
Down-converted output	Yes
Video output	3 x HDMI PGM 1 x STREAM (RJ-45)
Audio input	2x Balanced XLR 1x Stereo RCA (L/R) De-embedded Digital Audio
Audio output	1x Stereo headphone
Embedded audio support	Support for 2 channels of embedded audio
Audio delay calibration	N/A
A+V switching	N/A
USK/DSK	1x USK Lumakey
Picture in Picture (PiP)	1
Logo insertion	N/A
Built-in audio mixer	Master audio output control
Built-in monitor display	17.3" HD TFT LED backlit, 1920x1080 pix
Built in intercom/tally	Tally to connected cameras
Streaming audio/video encoding	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
Streaming protocol	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP (RTSP Elementary Streaming) RTMP/RTMPS (Publish)
Streaming settings control	Web browser UI for configuration and control Socket commands
Recording file system	FAT, exFAT, NTFS
Recording file format	MP4
Recording settings control	Web UI for system configuration and control
Special features	Built-in camera controller
Dimensions (LxWxH)	455 x 355 x 134 mm
Weight	17.2 Lbs (7.8 kg), Reinforce Plastic Case
Power	DC 48V, 4.16A
Operating temp. range	0~40 °C
Options	CB-60/61/62