

Model	FC-60B	FC-120B
Rated Power	78W	145W
Input Voltage/Current	DC15V/6A Max AC100-240V 50/60Hz	DC24V/6.25A Max AC100-240V 50/60Hz
Beam Angle	120°	
CCT	2700K-6500K	
CRI	Average 96	
TLCI	Average 98	
TM-30 Rf	Average 95	
TM-30 Rg	Average 101	
Dimming	0-100%	
Control	On-board, Remote Controller, NANLINK APP, DMX/RDM	
Special Effects	CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding	
product Size	Light Fixture (without COB protective cap): 169.2×106.4×180.4mm / 6.66×4.19×7.10" Power Adapter (without strap): 141×82×50mm / 5.55×3.23×1.97"	Light Fixture (without COB protective cap): 191.2×115×193.1mm / 7.53×4.53×7.60" Power Adapter (without strap): 160×64×30mm / 6.30×2.52×1.18"
Product Weight	Light Fixture: 0.7kg / 1.54lb Power Adapter: 0.45kg / 0.99lb Reflector: 0.08kg / 0.18lb	Light Fixture: 0.98kg / 2.16lb Power Adapter: 0.52kg / 1.15lb Reflector: 0.1445kg / 0.32lb
Certifications	CE, UKCA, RoHS, KCC, BIS, FCC-ID, NCC	

### Illumination (lux / fc)

#### FC-60B

##### Light Only

Distance	1M	3M	5M
2700K	2453 lux / 228 fc	301 lux / 28 fc	120 lux / 11 fc
3200K	2686 lux / 250 fc	330 lux / 31 fc	132 lux / 12 fc
5600K	3027 lux / 281 fc	372 lux / 35 fc	150 lux / 14 fc
6500K	2902 lux / 270 fc	354 lux / 33 fc	143 lux / 13 fc

With Reflector			
Distance	1M	3M	5M
2700K	10310 lux / 958 fc	987 lux / 92 fc	360 lux / 33 fc
3200K	11270 lux / 1047 fc	1087 lux / 101 fc	398 lux / 37 fc
5600K	12510 lux / 1162 fc	1228 lux / 114 fc	450 lux / 42 fc
6500K	11860 lux / 1102 fc	1170 lux / 109 fc	428 lux / 40 fc
With FL-11 Spot			
Distance	1M	3M	5M
2700K	26340 lux / 2447 fc	2444 lux / 227 fc	867 lux / 81 fc
3200K	29200 lux / 2713 fc	2710 lux / 252 fc	955 lux / 89 fc
5600K	32950 lux / 3061 fc	3075 lux / 286 fc	1078 lux / 100 fc
6500K	31540 lux / 2930 fc	2994 lux / 278 fc	1014 lux / 94 fc
With FL-11 Flood			
Distance	1M	3M	5M
2700K	6234 lux / 579 fc	730 lux / 68 fc	273 lux / 25 fc
3200K	6843 lux / 636 fc	803 lux / 75 fc	301 lux / 28 fc
5600K	7707 lux / 716 fc	904 lux / 84 fc	340 lux / 32 fc
6500K	7402 lux / 688 fc	860 lux / 80 fc	325 lux / 30 fc
With PJ-FMM-19			
Distance	1M	3M	5M
2700K	40880 lux / 3798 fc	3090 lux / 287 fc	1052 lux / 98 fc
3200K	44880 lux / 4169 fc	3399 lux / 316 fc	1158 lux / 108 fc
5600K	50660 lux / 4701 fc	3810 lux / 354 fc	1308 lux / 122 fc
6500K	48430 lux / 4499 fc	3642 lux / 338 fc	1255 lux / 117 fc
With PJ-FMM-36			
Distance	1M	3M	5M
2700K	14620 lux / 1358 fc	1160 lux / 108 fc	400 lux / 37 fc
3200K	16150 lux / 1500 fc	1280 lux / 119 fc	442 lux / 41 fc
5600K	18310 lux / 1701 fc	1461 lux / 136 fc	503 lux / 47 fc
6500K	17570 lux / 1632 fc	1410 lux / 131 fc	484 lux / 45 fc