

# Specifications

CCT Mode Power	50W+50W
Max Power Mode Power	100W
Runtime (Max Power Non-stop Output)	31min(when fully charged)
Color Temperature Range	2700K~6200K
CCT Mode 6200K/100% Illuminance (LUX)	1200(1 meter)(25°C temperature, indoor illuminance lower than 0.1lux, 1m test distance.)
Max Power Mode 4000K/100% Illuminance (LUX)	2300(1 meter)(25°C temperature, indoor illuminance lower than 0.1lux, 1m test distance.)
TLCI Index	≥97
CRI Index	≥96
Dimming Range	0~100%
LED Chip	324
HSI Mode	H: Hue 0° ~ 360°S: Saturation 0 ~ 100% INT: Intensity 0 ~ 100%
R Illuminance (LUX)	36 (1 meter)
G Illuminance (LUX)	100 (1 meter)
B Illuminance (LUX)	19 (1 meter)
Built-in Battery Capacity	Built-in Li-ion battery 6S/2600MAH
Charging Time (PD)	2H56MIN (20V/1.2A 25W )25°C temperature, the stick light is powered off to charge
Charging Time (DC)	3H3MIN (24V 25W ~ 28W )25°C temperature, the stick light is powered off to charge
Power Adapter Output Voltage/Current	24V/5A
Operation Temperature	-10° ~ 40°
Product Size	502*46*47 (W*D*H)
Net Weight	950g
Extension	1/4" Threaded Hole