

Model	<i>FS-150</i>
Rated Power	185W
LED Total Power	180W
Input Voltage/Current	AC100-240V 50/60Hz
CRI	96
TLCI	98
CCT	5600K
Dimming	0-100%
Control	On-board controller, 2.4G, Bluetooth
Effect	INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
Product Size	Light fixture( Without protective cap but with yoke): 356×213×115mm/14.02×8.39×4.53" Light fixture( Without protective cap and yoke): 288×137×115mm/11.34×5.39×4.53"
Product Weight	Light fixture:2.27kg/5.00lb Power cable 4.5M: 0.4kg/0.88lb Reflector: 0.2kg/0.44lb
Configuration	FS-150×1 Power cable 4.5M×1 Reflector×1 User manual×1
Certifications	CE, PSE, ETL, cETL, NCC, KUCAS, RoHS

### *Illumination(lux /fc)*

Distance	1M	2M	3M
Light only	6903 lux / 641 fc	1721 lux / 160 fc	814 lux / 76 fc
With reflector	26380 lux / 2451 fc	5651 lux / 525 fc	2422 lux / 225 fc
With Fresnel Lens flood	15920 lux / 1479 fc	3914 lux / 364 fc	1741 lux / 162 fc
With Fresnel Lens spot	54890 lux / 5099 fc	11360 lux / 1055 fc	4737 lux / 440fc