

Model	<i>FS-200B</i>
Rated Power	220W
Input Voltage/Current	AC100-240V 50/60Hz
CCT	2700K-6500K
CRI	Average 96
TLCI	Average 97
TM-30 Rf	95
TM-30 Rg	102
Dimming	0-100% continuous
Control	On-board, 2.4G, Bluetooth, NANLINK APP
Special Effects	CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
Product Size	Light fixture (without protective cap): 309 × 232 × 123mm / 12.17 × 9.13 × 4.84"
Product Weight	Light Fixture: 2.6kg / 5.73lb Power Cable 4.5M: 0.4kg / 0.88lb Reflector: 0.2kg / 0.44lb
Master Carton Size	520 × 520 × 495mm / 20.47 × 20.47 × 19.49"
Packing Quantity	4
Certifications	CE, UKCA, RoHS, KCC

Illumination (lux / fc)

Model	<i>FS-200B</i>		
Light Only			
Distance	1M	3M	5M
2700K	6237 lux / 579 fc	733 lux / 68 fc	297 lux / 28 fc
3200K	7845 lux / 729 fc	928 lux / 86 fc	376 lux / 35 fc
5600K	8578 lux / 797 fc	1021 lux / 95 fc	412 lux / 38 fc
6500K	7509 lux / 698 fc	888 lux / 82 fc	360 lux / 33 fc
With Reflector			
Distance	1M	3M	5M
2700K	21180 lux / 1968 fc	1940 lux / 180 fc	728 lux / 68 fc
3200K	26810 lux / 2491 fc	2456 lux / 228 fc	919 lux / 85 fc
5600K	29490 lux / 2740 fc	2731 lux / 254 fc	1016 lux / 94 fc
6500K	25800 lux / 2397 fc	2386 lux / 222 fc	881 lux / 82 fc
With FL-20G Spot			
Distance	1M	3M	5M
2700K	112000 lux / 10405 fc	10730 lux / 997 fc	3716 lux / 345 fc
3200K	142000 lux / 13192 fc	13650 lux / 1268 fc	4754 lux / 442 fc
4300K	158000 lux / 14678 fc	15270 lux / 1419 fc	5266 lux / 489 fc
5600K	140000 lux / 13006 fc	13420 lux / 1247 fc	4644 lux / 431 fc
With FL-20G Flood			
Distance	1M	3M	5M
2700K	17230 lux / 1601 fc	2081 lux / 193 fc	791 lux / 73 fc
3200K	21880 lux / 2033 fc	2626 lux / 244 fc	1007 lux / 94 fc
5600K	23900 lux / 2220 fc	2880 lux / 268 fc	1101 lux / 102 fc
6500K	20900 lux / 1942 fc	2512 lux / 233 fc	953 lux / 89 fc
With PJ-BM-19			
Distance	3M	5M	7M
2700K	10910 lux / 1014 fc	3696 lux / 343 fc	1804 lux / 168 fc
3200K	14260 lux / 1325 fc	4681 lux / 435 fc	2309 lux / 215 fc
5600K	16010 lux / 1487 fc	5203 lux / 483 fc	2538 lux / 236 fc
6500K	14000 lux / 1301 fc	4563 lux / 424 fc	2224 lux / 207 fc
With PJ-BM-36			
Distance	3M	5M	7M
2700K	4127 lux / 383 fc	1403 lux / 130 fc	705 lux / 65 fc
3200K	5180 lux / 481 fc	1783 lux / 166 fc	894 lux / 83 fc
5600K	5763 lux / 535 fc	1968 lux / 183 fc	991 lux / 92 fc
6500K	5000 lux / 464 fc	1722 lux / 160 fc	866 lux / 80 fc