

Model	FS-200
Rated Power	240W
LED Total Power	225W
Input Voltage/Current	AC100-240V 50/60Hz
CRI	96
TLCI	98
CCT	5600K
Dimming	0-100%
Control	On-board controller, 2.4G, Bluetooth
Effect	INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
Product Size	Light fixture( Without protective cap): 309 × 232 × 123mm / 12.17 × 9.13 × 4.84"
Product Weight	Light fixture: 2.48kg/5.47lb Power cable 4.5M: 0.4kg/0.88lb Reflector: 0.2kg/0.44lb
Configuration	FS-200×1 Power cable 4.5M×1 Reflector×1 User manual×1
Certifications	CE, PSE, ETL, cETL, NCC, KUCAS, ROHS

### *Illumination(lux /fc)*

Distance	1M	2M	3M
Light only	7852 lux / 729 fc	1978 lux / 184 fc	951 lux / 88 fc
With reflector	29380 lux / 2729 fc	6388 lux / 593 fc	2776 lux / 258 fc
With Fresnel Lens spot	53858 lux / 5003 fc	11216 lux / 1042 fc	4732 lux / 440 fc
With Fresnel Lens flood	18160 lux / 1687 fc	4527 lux / 421 fc	2027 lux / 188 fc