

Model	<i>FS-300B</i>
Rated Power	350W
Input Voltage/Current	AC100-240V 50/60Hz
CCT	2700K-6500K
CRI	Average 96
TLCI	Average 97
Dimming	0-100%
Control	On-board, 2.4G, Bluetooth, NANLINK APP
Special Effects	CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
Product Size	Light Fixture(without protective cap): 346 × 233 × 123mm / 13.62 × 9.17 × 4.84"
Product Weight	Light Fixture: 3.03kg / 6.68lb Power Cable 4.5M: 0.4kg / 0.88lb Reflector: 0.2kg / 0.44lb
Master Carton Size	505 × 480 × 460mm / 19.88 × 18.90 × 18.11"
Packing Quantity	4
Certifications	CE, UKCA, NCC, FCC-ID, ROHS, ETL, cETL

Illumination (lux / fc)

Model

FS-300B

Light Only

Distance	1M	2M	3M
2700K	9220 lux / 857 fc	2380 lux / 221 fc	1160 lux / 108 fc
3200K	11150 lux / 1036 fc	2891 lux / 269 fc	1406 lux / 131 fc
5600K	11130 lux / 1034 fc	2881 lux / 268 fc	1394 lux / 130 fc
6500K	9780 lux / 909 fc	2527 lux / 235 fc	1221 lux / 113 fc

With Reflector

Distance	1M	2M	3M
2700K	31630 lux / 2938 fc	6857 lux / 637 fc	2930 lux / 272 fc
3200K	38900 lux / 3614 fc	8465 lux / 786 fc	3529 lux / 328 fc
5600K	38720 lux / 3597 fc	8398 lux / 780 fc	3522 lux / 327 fc
6500K	34340 lux / 3190 fc	7354 lux / 683 fc	3127 lux / 290 fc

With FL-20G Spot

Distance	1M	2M	3M
2700K	127000 lux / 11798 fc	32060 lux / 2978 fc	8607 lux / 800 fc
3200K	159000 lux / 14771 fc	39270 lux / 3648 fc	10550 lux / 980 fc
5600K	158000 lux / 14678 fc	39140 lux / 3636 fc	10340 lux / 961 fc

6500K

139000 lux / 12913 fc

34330 lux / 3189 fc

9290 lux / 863 fc

With FL-20G Flood

Distance	1M	2M	3M
2700K	24560 lux / 2282 fc	6200 lux / 576 fc	2804 lux / 260 fc
3200K	29820 lux / 2770 fc	7545 lux / 701 fc	3401 lux / 316 fc
5600K	29510 lux / 2741 fc	7540 lux / 700 fc	3395 lux / 315 fc
6500K	24620 lux / 2287 fc	6595 lux / 613 fc	2970 lux / 276 fc

With PJ-FMM-19

Distance	1M	2M	3M
2700K	12600 lux / 1171 fc	4003 lux / 372 fc	1995 lux / 185 fc
3200K	15430 lux / 1433 fc	4922 lux / 457 fc	2446 lux / 227 fc
5600K	15300 lux / 1421 fc	4910 lux / 456 fc	2426 lux / 225 fc
6500K	13520 lux / 1256 fc	4364 lux / 405 fc	2158 lux / 200 fc

With PJ-FMM-36

Distance	1M	2M	3M
2700K	4452 lux / 414 fc	1503 lux / 140 fc	785 lux / 73 fc
3200K	5511 lux / 512 fc	1863 lux / 173 fc	974 lux / 90 fc
5600K	5497 lux / 511 fc	1856 lux / 172 fc	966 lux / 90 fc
6500K	4838 lux / 449 fc	1636 lux / 152 fc	848 lux / 79 fc

