

Model	Forza 500 II
Rated Power	560W
Input Voltage/Current	DC (Battery) 14.4V-26V/12A, AC100-240V 50/60Hz
Beam Angle	120°
CCT	5600K (G/M±80)
CRI	96
TLCI	97
TM-30 Rf	Average 95
TM-30 Rg	Average 102
Dimming	0-100%, by 0.1% increment
Control	On-board, Remote Controller, NANLINK APP, DMX/RDM
Special Effects	INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
Product Size	Light Fixture (without COB protective cap): 352 × 230 × 142mm / 13.9 × 9.1 × 5.6" Control Unit: 156 × 139 × 307mm / 6.1 × 5.5 × 12.1"
Product Weight	Light Fixture: 3.88kg / 8.55lb Control Unit: 3.58kg / 7.9lb AC Power Cable 6M: 0.55kg / 1.21lb DC Connection Cable 3M: 0.47kg / 1.04lb Quick Release Clamp: 0.6kg / 1.32lb Reflector: 0.2kg / 0.44lb
Master Carton Size	560 × 390 × 630mm / 21.7 × 15.0 × 24.0"
Packing Quantity	2
Certifications	CE, UKCA, RoHS

Illumination (lux / fc)

Distance	1M	3M	5M
Light Only	22550 lux	2715 lux	1120 lux
	2095 fc	252 fc	104 fc
With Reflector	92310 lux	8376 lux	3030 lux
	8576 fc	778 fc	281 fc
Distance	3M	5M	7M
With FL-20G Spot	20860 lux	7311 lux	3675 lux
	1938 fc	679 fc	341 fc
With FL-20G Flood	6744 lux	2576 lux	1410 lux
	627 fc	239 fc	131 fc
With PJ-BM-19	21010 lux	6818 lux	3260 lux
	1952 fc	633 fc	303 fc
With PJ-BM-36	7463 lux	2526 lux	1275 lux
	693 fc	235 fc	118 fc