

Model	<i>Forza 150B</i>
Rated Power	170W
Input Voltage/Current	DC24V/7.5A Max, AC100-240V 50/60Hz
CCT	2700K-6500K
CRI	Average 96
TLCI	Average 98
TM-30 Rf	Average 93
TM-30 Rg	Average 102
Dimming	0-100%
Control	On-board, 2.4G, Bluetooth, NANLINK APP, DMX/RDM
Special Effects	CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
Product Size	Light Fixture(without protective cap): 247 × 133 × 115mm / 9.72 × 5.24 × 4.53" Power Adapter(with base): 167 × 80 × 45mm / 6.57 × 3.15 × 1.77"
Product Weight	Light Fixture: 1.56kg / 3.44lb Power Adapter: 0.67kg / 1.48lb Power Cable 4.5M: 0.4kg / 0.88lb Reflector: 0.14kg / 0.31lb Bowens Mount Adapter: 0.19kg / 0.42lb
Master Carton Size	555 × 445 × 535mm / 21.85 × 17.52 × 21.06"
Packing Quantity	4
Certifications	CE, UKCA, ROHS, FCC-ID, NCC

Illumination (lux / fc)

Model	<i>Forza 150B</i>		
Light Only			
Distance	1M	2M	3M
2700K	3824 lux / 355 fc	1019 lux / 95 fc	492lux / 46 fc
3200K	4170 lux / 387 fc	1127 lux / 105 fc	520 lux / 48 fc
5600K	5121 lux / 476 fc	1352 lux / 126 fc	644 lux / 60 fc
6500K	5223 lux / 485 fc	1381 lux / 128 fc	654 lux / 61 fc

With Reflector

Distance	1M	2M	3M
2700K	17500 lux / 1626 fc	3874 lux / 360 fc	1600 lux / 149 fc
3200K	18860 lux / 1752 fc	4084 lux / 379 fc	1753 lux / 163 fc
5600K	23130 lux / 2149 fc	4826 lux / 448 fc	2078 lux / 193 fc
6500K	23660 lux / 2198 fc	5026 lux / 467 fc	2135 lux / 198 fc

With FL-11 Spot

Distance	1M	2M	3M
2700K	41300 lux / 3837 fc	9800 lux / 910 fc	4290 lux / 399 fc
3200K	45370 lux / 4215 fc	10800 lux / 1003 fc	4732 lux / 440 fc
5600K	54290 lux / 5044 fc	13050 lux / 1212 fc	5721 lux / 531 fc
6500K	55500 lux / 5156 fc	13110 lux / 1218 fc	5813 lux / 540 fc

With FL-11 Flood

Distance	1M	2M	3M
2700K	9350 lux / 869 fc	2390 lux / 222 fc	1087 lux / 101 fc
3200K	10300 lux / 957 fc	2630 lux / 244 fc	1187 lux / 110 fc
5600K	12460 lux / 1158 fc	3150 lux / 293 fc	1444 lux / 134 fc
6500K	12750 lux / 1184 fc	3206 lux / 298 fc	1466 lux / 136 fc

With PJ-FMM-19

Distance	1M	2M	3M
2700K	59360 lux / 5515 fc	10590 lux / 984 fc	4224 lux / 392 fc
3200K	64480 lux / 5990 fc	11680 lux / 1085 fc	4605 lux / 428 fc
5600K	76560 lux / 7112 fc	14000 lux / 1301 fc	5594 lux / 520 fc
6500K	77550 lux / 7204 fc	14300 lux / 1328 fc	5700 lux / 530 fc

With PJ-FMM-36

Distance	1M	2M	3M
2700K	23450 lux / 2179 fc	4437 lux / 412 fc	1871 lux / 174 fc
3200K	25600 lux / 2378 fc	4982 lux / 463 fc	1972 lux / 183 fc
5600K	30700 lux / 2852 fc	5920 lux / 550 fc	2467 lux / 229 fc
6500K	31090 lux / 2888 fc	6019 lux / 559 fc	2522 lux / 234 fc