

HS-1300 6-Channel HD Portable Video Streaming Studio

Video Standard	HD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60Hz
Input Routable / Crosspoint	All 6, repeatable
Video Input	4 x HD-SDI 2 x HDMI
Computer Graphic Interface	2 via HDMI
Down-converted Output	N/A
Video Output	3x HDMI 2x SDI assignable: AUX 1-6, PGM, PVW, PGM Clean or Multiview
Audio Input	2x Balanced XLR
Audio Output	1x Stereo headphone
Digital Embedded Audio Support Input	Input 2 channels, Output 2 channels
A+V Switching	Yes
USK	2x USK support Chromakey
DSK	2, support Lumakey & Linear key (Key / Fill)
Picture in Picture	1
Logo Insertion	N/A
Built-in Audio Mixer	N/A
Built-in Monitor Display	17.3" HD TFT LED backlit, 1600x900 pix
Built-in Intercom & Tally	N/A
Streaming Video Encode	H.264 / AVC, Main/ High Profile Configurable Bit-rate up to 10Mbps
Streaming Audio Encode	AAC-LC Configurable bit rate range from 32Kbps to 384Kbps Sample rate: 48KHz, 16bit
Streaming Protocol	TS over TCP/UDP (unicast & multicast) RTSP over HTTP/TCP/UDP RTMP/RTMPS (Publish)
Streaming Control	Web browser UI for configuration and control Socket commands
Recording File System	FAT, exFAT, NTFS
Recording File Format	MP4
Recording Setting Control	Web UI for system configuration and control
Special Features	Streaming encoder and recorder 2 chromakey virtual studio 9 stinger transition and 30 virtual sets included
Dimension (LxWxH)	455 x 355 x 134 mm
Weight	16.3 Lbs (7.4 kg), Reinforce Plastic Case
Power	DC 12V, 5A
Operating Temp. Range	0~40 °C
Options	CB-22H/23H/46/47/60/61/62
What's in the Box	
Content	1 x HS-1300 Product 1 x AD Switch DC 12V with AC Cord 1 x Thank You Card
Drive Compatibility	For a list of verified compatible drives, visit the Drive Compatibility Page