

Technical Data

Model	<i>PavoSlim 60CL</i>
Rated Power	72W
Input Voltage/Current	DC(Battery)14.4-26V DC(Battery)7.4V × 2 AC100-240V 50/60Hz
CCT	2700K-7500K(G/M ± 150)
CRI	Average 96
TLCI	Average 97
TM-30 Rf	Average 94
TM-30 Rg	Average 100
SSI (3200K)	83
SSI (5600K)	74
Dimming	0-100%
LED Type	RGBWW
Control	On-board, Remote Controller, NANLINK APP, LumenRadio CRMX, DMX/RDM
Special Effects	HUE Loop, CCT Loop, INT Loop, Flash, Pulse, Storm, Police Car, TV, Paparazzi, Candle/Fire, Disco, Bad Bulb, Firework, Explosion and Welding
Product Size	Light Fixture: 602 × 152 × 18.6mm / 23.70 × 5.98 × 0.73" Control Unit: 146.45 × 111.48 × 175mm / 5.77 × 4.39 × 6.89"
Product Weight	Light Fixture: 0.98kg / 2.16lb Control Unit: 1.37kg / 3.02lb
Certifications	CE, UKCA, RoHS, PSE, KCC, BIS, FCC-ID, ETL+cETL, NCC

Illumination (lux / fc)

PavoSlim 60CL

Light Only

Distance	0.5M	1M	3M
2700K	18430 lux / 1712 fc	5857 lux / 544 fc	735 lux / 68 fc
3200K	18700 lux / 1737 fc	6012 lux / 559 fc	750 lux / 70 fc
5600K	22110 lux / 2054 fc	7094 lux / 659 fc	880 lux / 82 fc
7500K	21590 lux / 2006 fc	6952 lux / 646 fc	864 lux / 80 fc
R	8280 lux / 769 fc	2432 lux / 226 fc	305 lux / 28 fc
G	15080 lux / 1401 fc	4445 lux / 413 fc	525 lux / 49 fc
B	2210 lux / 205 fc	660 lux / 61 fc	76 lux / 7 fc

With Softbox and Lite Diffuser

Distance	0.5M	1M	3M
2700K	9300 lux / 864 fc	2577 lux / 239 fc	296 lux / 27 fc
3200K	9550 lux / 887 fc	2651 lux / 246 fc	304 lux / 28 fc
5600K	11280 lux / 1048 fc	3130 lux / 291 fc	359 lux / 33 fc
7500K	11000 lux / 1022 fc	3056 lux / 284 fc	350 lux / 33 fc
R	4950 lux / 460 fc	1362 lux / 127 fc	155 lux / 14 fc
G	8970 lux / 833 fc	2466 lux / 229 fc	280 lux / 26 fc
B	1320 lux / 123 fc	358 lux / 33 fc	41 lux / 4 fc

With Softbox and Standard Diffuser

Distance	0.5M	1M	3M
2700K	4891 lux / 454 fc	1219 lux / 113 fc	139 lux / 13 fc
3200K	4988 lux / 463 fc	1238 lux / 115 fc	141 lux / 13 fc
5600K	5905 lux / 549 fc	1465 lux / 136 fc	167 lux / 16 fc
7500K	5771 lux / 536 fc	1423 lux / 132 fc	163 lux / 15 fc
R	2610 lux / 242 fc	644 lux / 60 fc	73 lux / 7 fc
G	4686 lux / 435 fc	1165 lux / 108 fc	132 lux / 12 fc
B	720 lux / 67 fc	177 lux / 16 fc	20 lux / 2 fc