

Model	PavoSlim 60C	PavoSlim 120C
Rated Power	72W	150W
Input Voltage/Current	DC(Battery)14.4-26V DC(Battery)7.4V × 2 AC100-240V 50/60Hz	DC24V DC(Battery)14.4-26V AC100-240V 50/60Hz
CCT	2700K-7500K(G/M ± 150)	
CRI	Average 96	
TLCI	Average 97	
TM-30 Rf	Average 94	
TM-30 Rg	Average 100	
SSI (3200K)	83	
SSI (5600K)	74	
Dimming	0-100%	
LED Type	RGBWW	
Control	On-board, Remote Controller, NANLINK APP, LumenRadio CRMX, DMX/RDM	
Special Effects	HUE Loop, CCT Loop, INT Loop, Flash, Pulse, Storm, Police Car, TV, Paparazzi, Candle/Fire, Disco, Bad Bulb, Firework, Explosion and Welding	
Product Size	Light Fixture: 306.3 × 300.65 × 18.6mm / 12.06 × 11.84 × 0.73" Control Unit: 146.45 × 111.48 × 175mm / 5.77 × 4.39 × 6.89"	Light Fixture: 602 × 306.3 × 18.6mm / 23.7 × 12.06 × 0.73" Control Unit: 140.3 × 111.48 × 203mm / 5.52 × 4.39 × 7.99"
Product Weight	Light Fixture: 0.94kg / 2.07lb Control Unit: 1.37kg / 3.02lb	Light Fixture: 1.76kg / 3.88lb Control Unit: 1.84kg / 4.06lb
Certifications	RoHS, CE, UKCA, FCC-ID, NCC, KCC	

Illumination (lux / fc)

PavoSlim 60C

Light Only

Distance	0.5M	1M	3M
2700K	20780 lux / 1930 fc	5912 lux / 549 fc	717 lux / 67 fc
3200K	22310 lux / 2073 fc	6362 lux / 591 fc	769 lux / 71 fc
5600K	24900 lux / 2313 fc	7074 lux / 657 fc	849 lux / 79 fc
7500K	23700 lux / 2202 fc	6728 lux / 625 fc	809 lux / 75 fc
R	9530 lux / 885 fc	2580 lux / 240 fc	305 lux / 28 fc
G	17520 lux / 1628 fc	4595 lux / 427 fc	544 lux / 51 fc
B	2510 lux / 233 fc	660 lux / 61 fc	78 lux / 7 fc

With Softbox and Lite Diffuser

Distance	0.5M	1M	3M
2700K	10250 lux / 952 fc	2528 lux / 235 fc	290 lux / 27 fc
3200K	11130 lux / 1034 fc	2732 lux / 254 fc	313 lux / 29 fc
5600K	12360 lux / 1148 fc	3034 lux / 282 fc	349 lux / 32 fc
7500K	11820 lux / 1098 fc	2885 lux / 268 fc	332 lux / 31 fc
R	5090 lux / 473 fc	1233 lux / 115 fc	148 lux / 14 fc
G	9604 lux / 892 fc	2308 lux / 214 fc	268 lux / 25 fc
B	1400 lux / 130 fc	334 lux / 31 fc	39 lux / 4 fc

With Softbox and Standard Diffuser

Distance	0.5M	1M	3M
2700K	5648 lux / 525 fc	1250 lux / 116 fc	138 lux / 13 fc
3200K	6161 lux / 572 fc	1356 lux / 126 fc	149 lux / 14 fc
5600K	6787 lux / 631 fc	1525 lux / 142 fc	166 lux / 15 fc
7500K	6452 lux / 599 fc	1444 lux / 134 fc	158 lux / 15 fc
R	2885 lux / 268 fc	664 lux / 62 fc	73 lux / 7 fc
G	5455 lux / 507 fc	1202 lux / 112 fc	132 lux / 12 fc
B	810 lux / 75 fc	178 lux / 17 fc	19 lux / 2 fc

PavoSlim 120C

Light Only

Distance	0.5M	1M	3M
2700K	29550 lux / 2745 fc	10500 lux / 975 fc	1388 lux / 129 fc
3200K	31750 lux / 2950 fc	11200 lux / 1040 fc	1475 lux / 137 fc
5600K	36240 lux / 3367 fc	12830 lux / 1192 fc	1675 lux / 156 fc
7500K	34450 lux / 3200 fc	12240 lux / 1137 fc	1594 lux / 148 fc
R	15500 lux / 1440 fc	5100 lux / 474 fc	641 lux / 60 fc
G	27300 lux / 2536 fc	8655 lux / 804 fc	1063 lux / 99 fc
B	3830 lux / 356 fc	1290 lux / 120 fc	156 lux / 14 fc

With Softbox and Lite Diffuser

Distance	0.5M	1M	3M
2700K	17360 lux / 1613 fc	4850 lux / 451 fc	579 lux / 54 fc
3200K	18570 lux / 1725 fc	5191 lux / 482 fc	621 lux / 58 fc
5600K	21320 lux / 1981 fc	5944 lux / 552 fc	711 lux / 66 fc
7500K	20050 lux / 1863 fc	5624 lux / 522 fc	670 lux / 62 fc
R	9150 lux / 850 fc	2573 lux / 239 fc	296 lux / 27 fc
G	16680 lux / 1550 fc	4536 lux / 421 fc	536 lux / 50 fc
B	2590 lux / 241 fc	780 lux / 72 fc	90 lux / 8 fc

With Softbox and Standard Diffuser

Distance	0.5M	1M	3M
2700K	10420 lux / 968 fc	3460 lux / 229 fc	290 lux / 27 fc
3200K	11160 lux / 1037 fc	2635 lux / 245 fc	312 lux / 29 fc
5600K	12720 lux / 1182 fc	3026 lux / 281 fc	357 lux / 33 fc
7500K	12050 lux / 1119 fc	2856 lux / 265 fc	337 lux / 31 fc
R	5650 lux / 525 fc	1334 lux / 124 fc	161 lux / 15 fc
G	10120 lux / 940 fc	2380 lux / 221 fc	281 lux / 26 fc
B	1650 lux / 153 fc	375 lux / 35 fc	53 lux / 5 fc