

Model	PavoTube II 15C
Rated Power	30W
Input Voltage/Current	DC15V/2A Max, AC100-240V 50/60Hz PD3.0(9-20V)20W Min
CCT	2700K-7500K(G/M±150)
CRI	Average 97
TLCI	Average 98
TM-30 Rf	Average 94
TM-30 Rg	Average 101
Dimming	0-100%
Control	On-board, 2.4G, Bluetooth, NANLINK APP, DMX/RDM
Effect	Hue Loop, CCT Loop, INT Loop, CCT Flash, HUE Flash, CCT Pulse, Hue Pulse, Storm Auto, Police Car, TV, Paparazzi, Candle/Fire, Disco, Bad Bulb, Firework, Explosion and Welding
Product Size	φ48 × 770mm / φ1.89 × 30.31"
Product Weight	Light Fixture: 0.85kg / 1.87lb Power Adapter: 0.2kg / 0.44lb Power Cable 3M: 0.05kg / 0.11lb
Master Carton Size	605 × 305 × 890mm / 23.82 × 12.01 × 35.04" (1KIT) 455 × 305 × 890mm / 17.91 × 12.01 × 35.04" (2KIT) 365 × 185 × 885mm / 14.37 × 7.28 × 34.84" (4KIT)
Quantity of Boxes Per Carton	1KIT: 8 / 2KIT: 6 / 4KIT: 2
Certification	CE, UKCA, RoHS, PSE, KCC, FCC-ID, NCC, KC

Illumination (lux / fc)

Distance	0.5M	1M	2M	3M
2700K	1231 lux	374 lux	103 lux	48 lux
	114 fc	35 fc	10 fc	4 fc
3200K	1335 lux	391 lux	107 lux	50 lux
	124 fc	36 fc	10 fc	5 fc
5600K	1428 lux	423 lux	113 lux	55 lux
	133 fc	39 fc	10 fc	5 fc
6500K	1460 lux	428 lux	117 lux	58 lux
	136 fc	40 fc	11 fc	5 fc
7500K	1442 lux	427 lux	115 lux	56 lux
	134 fc	40 fc	11 fc	5 fc
R	601 lux	181 lux	50 lux	24 lux
	56 fc	17 fc	5 fc	2 fc
G	1338 lux	395 lux	108 lux	54 lux
	124 fc	37 fc	10 fc	5 fc
B	219 lux	69 lux	19 lux	9 lux
	20 fc	6 fc	2 fc	1 fc