


# Solidcom C1 Pro - Roaming Hub

## Stay Connected, Roam Freely


Designed with the expressed needs of customers in mind, Solidcom C1 Pro - Roaming Hub boasts support for up to 20 headsets and 6 groups, seamless roaming, an extensive range of 1,600ft (500m), and backward compatibility, among other powerful functions and features. This innovative solution will definitely empower people across all styles of communication settings, including filmmaking and video production, and take their communication experience to new heights.



20-User  
Connectivity



1,600ft (500m)  
LOS Range



Seamless  
Roaming



6-Group Talking



USB Audio Class  
(UAC)



App Control



## I Specifications

	Hub
LOS Range	1,600ft (500m)
Operating Frequency	1904 - 1919 MHz: China 1880 - 1900 MHz: Europe, South Africa, much of Asia, Hong Kong SAR, Australia, and New Zealand (10 channels) 1880 - 1895 MHz: Taiwan (8 channels) 1893 - 1906 MHz: Japan (J-DECT) 1910 - 1920 MHz: Brazil (10 channels) 1910 - 1930 MHz: Much of Latin America excluding Brazil. 1920 - 1930 MHz: USA & Canada
Transmit Power	≤ 21 dBm
Bandwidth	1.728 MHz
Modulation Mode	GFSK
Frequency Response	100 Hz - 7 kHz (±3dB) @1 kHz
Receiver Sensitivity	≤ -90 dBm
SNR	> 55dB
Antenna Gain	4 dBi (all directions)
DC Voltage Range	7 - 30V, < 1A@12V
V/G Mount Battery Voltage Range	11 - 30V, < 1A@12V
Power Consumption	< 1A@12V
Dimensions	302mm × 181.52mm × 63.6mm
Weight	1797.5g (63.4oz)
Temperature Range	-10 - 45°C (working) -20 - 60°C (storage)

Note: Due to differences in various countries and regions, there may be variations in the operating frequency and wireless transmit power of the product.