





Product Comparison

Item	 Solidcom C1 Pro (Without Hub)	 Solidcom C1 Pro (With Hub)	 Solidcom C1 (Without Hub)	 Solidcom C1 (With Hub)
Transmission Range	1, 100ft (350m)	1, 100ft (350m)	1, 100ft (350m)	1, 100ft (350m)
Full Duplex	Yes	Yes	Yes	Yes
ENC	Yes	Yes	No	No
PTT	Yes	Yes	No	No
Group Function	No	Yes (Max two groups)	No	Yes (Max two groups)
2W	No	Yes XLR (IN/OUT)	No	Yes XLR (IN/OUT)
4W	No	Yes RJ45 (IN/OUT)	No	Yes RJ45 (IN/OUT)
Cascade	No	Unlimited (Cascade via 4W and IP digital signal)	No	Unlimited (Cascade via 4W and IP digital signal)
Antenna	Built-in	External	Built-in	External
Frequency Band	1.9GHz	1.9GHz	1.9GHz	1.9GHz
Power Supply	Headset: Rechargeable and replaceable lithium battery (Each headset comes with 2 batteries.)	Headset: Rechargeable and replaceable lithium battery (Each headset comes with 2 batteries.) Hub: NP-F battery, V-mount battery, G-mount battery, DC power	Headset: Rechargeable and replaceable lithium battery (Each headset comes with 2 batteries.)	Headset: Rechargeable and replaceable lithium battery (Each headset comes with 2 batteries.) Hub: NP-F battery, V-mount battery, G-mount battery, DC power
Package	2-person intercom system to 8-person intercom system	9-person intercom system	2-person intercom system to 8-person intercom system	9-person intercom system

Note:

1. The frequency bands of different countries or regions may be different. Please consult Hollyland for specific information.

2. The master headset of the Solidcom series intercom systems cannot be used in a hub-based system.