

Specifications

Stabilizer

Tilt Mechanical Range 310°

Roll Mechanical Range 340°

Pan Mechanical Range 360°

Battery

Operation Voltage Max: 8.4v / Min: 6.5v

Operation Current Max: 5300mA / Min: 150mA

Output 5V, 1A

Battery Runtime Max: 11.5h (lab data)

Charging Time 2h (lab data)

Size & Weight

Product Size (W*D*H) 305*210*72.5 (mm)

Net Weight 1054.8g/unit

Camera Compatibility List

Sony A1, A9, A9II, A7M2, A7R2, A7S2, A7M3, A7M4, A7R3, A7R4, A7R5, A7S3, A7C, A6600, A6500, A6400, A6300, A6100, ZV-E10, ZV-E1, ZV-1, ILME-FX3

Nikon D850, D780, Z fc, Z50, Z5, Z6, Z6 II, Z7, Z7 II, Z30, Z8

Canon 5DS, 5DS R, 5D MIII, 5D MIV, 6D MII, 6D, 80D, 90D, 800D, 850D, 200D II, R50, R, R5, R6, RP, R7, R8, R10, M50, M6 MII

Panasonic G9, GH5, GH5s, GH6, S5, S1, S1H

OLYMPUS BMPCC 4K, BMPCC 6K

FUJIFILM X-T3, X-T4, X-T5, X-H2s

ZCAM E2

SIGMA FP